



*** PINOUT DIAGRAM ***

J1	J2	J3
1	1	1
2	2	2
3	3	3
4	4	4
5	5	5
:	:	:
:	:	:
:	:	:
:	:	:
:	:	:
:	:	:
36	36	36
37	37	37
38	38	38
39	39	39
40	40	40

BILL OF MATERIAL

①	FLAT CABLE UL2651 28AWG(7/0.127mm) HF-40P, DD: 0.9*0.127mm JACKET GRAY COLDR.	1 m r
②	I.D.C SOCKET 40P WITH CENTER POLARIZATION, AND WITHDUT S/R & NOSE.(兩件式) INSULATOR: PBT GLASS-FIBER REINFORCED UL94V-0. CONTACT: BRONZE GOLD FLASH OVER NICKEL.	3 pcs

NO.	SPECIFICATION	Q'TY
-----	---------------	------

REVISION LIST		DRAWG BY	APPROVED BY
REV	DESCRIPTION	DATE	CHECK BY
A	INITIAL RELEASE DF DWG	NOV.17.2001	

TOLERANCE: .XX= .XXX=	SCALE: NONE	UNIT: mm
--------------------------	----------------	-------------

PART NO:	DWG NO:	REV:
CUST NO:	CK111062	A
TITLE :	HDD FLAT CABLE	
SHEET 1 OF 1		