



TEST:
1.100% OPEN&SHORT WITH MISS WIRE TEST
2.TEST CONDITION:
1).CONDUCTANCE RESISANCE:5Ω
2).SHORT OPEN DETERMINANT:50 KΩ
3).INSULATION RESISTANCE: 50MΩ AT DC 500V.

WIRE LIST:

CN1	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
CN2	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25

		APPROVALS		DATE		TITLE																	
		DRAWN		未世全		05/04/04		DB 25M TO DB 25F CABLE NL=200mm															
		CHECKED																					
		APPROVED				SCALE N.A. SHEET 1 OF 1																	
3		DB 25/MALE IDC TYPE CONTACT G/F TIN SHELL BLACK				1SET																	
2		DB 25/FEMALE IDC TYPE CONTACT G/F TIN SHELL WITH 4-40UNC BLACK				1SET																	
1		UL2651 28AWG(7/0.127)*25C PITCH 1.27mm PVC JACKET COLOR GRAY				1PC																	
ITEM		DESCRIPTION				Q'TY						UNIT		MM		SIZE		PART NO.		DRAWING NO.		REV.	
																FLAT-DB25MF0.2		04050406-00		AX1			